

The ergonomically designed SLS25XP stapler is powerful and versatile. This stapler weighs just 2.7 pounds, yet has the power to drive 1½" staples into hard woods. Two models drive ¼" and ⅜" crown staples in lengths from ⅜" to 1½".



**XP**  
XTREMEPRO™



### Applications:

For varied component assemblies in furniture manufacturing, such as drawers, casebacks, cabinet frame assembly and upholstery spring attachment. Used in underlayment sheathing, paneling, molding/trim, soffits, prefinished gypsum and siding for on-site and manufactured housing. Used in a variety of general woodworking and wood assembly operations, including lattice and bed-spring attachment.

### Features and Benefits:

- Lightweight (2.7 lbs.) for ease of handling
- Ergonomically designed with a comfort-grip handle to reduce fatigue
- Adjustable depth-of-drive for precise staple setting
- 40% more power than comparable tools
- Heavy duty components, including an aluminum sleeve and piston, mean rugged durability even in high volume production environments
- No-mar pad keeps work surfaces free of marks
- Oil-free design means easier maintenance and no lubrication to stain fine wood
- Muffler ensures quiet operation
- Either Dual Action or Restrictive Trigger\* available, depending on whether repetitive high productivity or precision fastener placement is more important

### Tool Specifications:

Item #: SLS25XP-L: 820103N Contact Actuation  
SLS25XP-M: 820107N Contact Actuation  
Tool Weight: 2.7 lbs (1.1 kg)  
Height: 9" (229 mm)  
Length: 12" (305 mm)  
Staple Capacity: 145–168  
Reg. Operating Pressure: 70-120 psig (4.8-8.3 bar)  
Mode of Operation: Contact or Sequential Actuation

### Fastener Specifications:

Available Crown Widths ¼", ⅜"  
Lengths: ⅜" – 1-1/2"

